



INSTALLATION INSTRUCTIONS

P/N 26100 DISTRIBUTOR TIMING INDICATOR

Fits all V-8 and V-6 Chevy, Accel, Accel B.E.I. and Mallory Distributors.

Remove distributor and place degreed plate between distributor and intake manifold. Secure with screws provided. (Be sure to apply Loctite to screws.) Place pointer assembly around distributor housing and reinstall onto motor.

Time engine in usual manner. Secure pointer at 0°. This will provide a quick and easy reference if you wish to vary your timing a few degrees.

Remember, the calibrations are marked for **DISTRIBUTOR** degrees, and the thickness of the indicator plate is .062" This thickness **MUST** be taken into consideration to ensure proper oil pump drive engagement.

PARTS LIST

- | | |
|---|-------------------------------------|
| 1 | 8-32 X 3/4" SHCS |
| 1 | TIMING INDICATOR PLATE, GOLD |
| 1 | TIMING INDICATOR ASSEMBLY |
| 2 | 8-32 X 1/4 FLAT HEAD SCREW, SLOTTED |

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437-2116
Phone: (203) 453-6571 • Fax: (203) 453-6906