

CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7162  
ENGINE: Chevrolet 396-454 c.i.d. V8  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5762. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 300°	Exhaust 306°
Duration at .050" Lift:	Intake 240°	Exhaust 246°
Lift at cam:	Intake .330"	Exhaust .337"
Lift at valve:	Intake .560"	Exhaust .573"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	50° ABDC
Exhaust	57° BBDC	9° ATDC
Centerlines:	Intake: 110°	
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7162*  
*Rev. 1/06*

*©2006 Edelbrock Corporation*  
*Brochure #63-0486*

CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7162  
ENGINE: Chevrolet 396-454 c.i.d. V8  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5762. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 300°	Exhaust 306°
Duration at .050" Lift:	Intake 240°	Exhaust 246°
Lift at cam:	Intake .330"	Exhaust .337"
Lift at valve:	Intake .560"	Exhaust .573"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	50° ABDC
Exhaust	57° BBDC	9° ATDC
Centerlines:	Intake: 110°	
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7162*  
*Rev. 1/06*

*©2006 Edelbrock Corporation*  
*Brochure #63-0486*

CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7162  
ENGINE: Chevrolet 396-454 c.i.d. V8  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5762. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 300°	Exhaust 306°
Duration at .050" Lift:	Intake 240°	Exhaust 246°
Lift at cam:	Intake .330"	Exhaust .337"
Lift at valve:	Intake .560"	Exhaust .573"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	50° ABDC
Exhaust	57° BBDC	9° ATDC
Centerlines:	Intake: 110°	
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7162*  
*Rev. 1/06*

*©2006 Edelbrock Corporation*  
*Brochure #63-0486*

CAMSHAFT: Performer RPM Hydraulic  
CATALOG #7162  
ENGINE: Chevrolet 396-454 c.i.d. V8  
RPM RANGE: 1500-6500

CAUTION: Do not use dual valve springs. Use recommended Edelbrock Sure Seat or equivalent valve springs #5762. Use stock ratio rocker arms only.

Duration at .006" Lift:	Intake 300°	Exhaust 306°
Duration at .050" Lift:	Intake 240°	Exhaust 246°
Lift at cam:	Intake .330"	Exhaust .337"
Lift at valve:	Intake .560"	Exhaust .573"
Timing at .050 Lift:	Open	Close
Intake	10° BTDC	50° ABDC
Exhaust	57° BBDC	9° ATDC
Centerlines:	Intake: 110°	
Lobe Separation:	112°	

CAUTION: Use Edelbrock Performer-Link Timing Chain and Gear Set #7810 or Accu-Drive gear drive #7891. Do not use late model timing chain and gear sets that are designed for emission-controlled engines. These timing sets are machined in a retarded position and are not recommended for this camshaft installation. Edelbrock Timing Sets feature three keyways for specified timing selection. Use "0" position for most applications.

*Catalog #7162*  
*Rev. 1/06*

*©2006 Edelbrock Corporation*  
*Brochure #63-0486*