



**PART NO. 16764HKR**  
**HEADER H-PIPE / BALANCE TUBE ASSEMBLY**  
**1979-93 Mustang & Mustang II (255-302W)**  
**1979-85 Mercury Capri (255-302W)**

**NOTE:** This H-pipe is designed to fit with Hooker P/N 6222HKR & 6222-1HKR only.

**NOTE:** This H-pipe will bolt to stock Ford exhaust or P/N 16861HKR catback exhaust system.

**NOTE:** Will fit the 1979-85 Mustangs, if retrofitted with the late model "double hump" transmission crossmember.

Thank you for making HOOKER HEADERS your choice in a high-performance exhaust system. Extensive dyno/track testing has enabled HOOKER to offer the most advanced design in exhaust systems. The installation, while not complex, will take a certain amount of time. However, the additional horsepower and improved performance will more than justify your efforts. Proper installation and maintenance will ensure long life and maximum performance from your HOOKER HEADER exhaust system.

**WARNING!** Breaking in an engine with ceramic-coated headers **WILL** result in damage to the coating and will **VOID** all warranties. Ceramic-coated headers require several heat cycles to fully cure before they will withstand extreme heat. HOOKER recommends using a cast-iron exhaust manifold or an old header to break in new engines to avoid coating damage.

**BEFORE STARTING**

Your vehicle must be raised a minimum of 36 inches. A floor hoist is ideal. If no hoist is available, we strongly urge the use of axle stands as a safety measure.

**CAUTION! YOUR CAR SHOULD NOT BE SUPPORTED ON A BUMPER JACK.**

**NOTE:** We recommend welding all pipe slip joints. If no welding equipment is available at the time of installation, use the furnished clamps to secure the pipes, until they can be welded.

**INSTALLATION PROCEDURE – PLEASE READ CAREFULLY**

1. Install Hooker Header P/N 6222HKR per its instructions.
2. Slide the H-pipe sections together and loosely install the supplied muffler clamp.
3. Place the gasket between the header collectors and the H-pipe. Install the H-pipe into place.
4. Bolt the rear of the H-pipe to the stock Mustang exhaust or Hooker P/N 16861HKR Catback Exhaust System.
5. Starting at the collectors, tighten all the bolts evenly, working rearward.

When finished, give your vehicle a test drive, checking carefully for any new noises. After several days of driving, retighten all the bolts.

Any questions? Please contact Technical Service: 1-866-GOHOLLEY or 270-781-9741. For online help, please refer to the website: [www.holley.com](http://www.holley.com).

**LIMITATION OF LIABILITY – DISCLAIMER:**

The regulation of emissions production, noise levels, and safety standards is undertaken by the federal government, each of the fifty state legislatures, and by many local municipalities, towns, and counties.

HOOKER makes no warranties of merchantability, of fitness for particular purpose, or that its products are approved for general use, or that its products are approved for general use, or that its products comply with laws, regulations, or ordinances in the state where they may be sold to the ultimate purchaser, the consumer.

Unless expressly stated to the contrary in the catalog, instruction sheet; or price list, the entire risk as to the conformity of any company product in any such state and as to repair should the product prove to be defective or non-conforming, is on the retail purchaser, the buyer, the ultimate consumer, of such product and it is not upon the seller, distributor, or manufacturer.

In this connection, the retail purchaser, the buyer, the ultimate consumer assumes the burden of the entire cost of any and all necessary service, alterations, or repair.

**THE FOREGOING STATEMENT LIMITS THE LIABILITY OF THE MANUFACTURER.**

California vehicle code, sections 27156 AND 38391, prohibit the advertising, offering for sale, or installation of any device, which modifies a vehicle's emission control system, unless exempted, unless otherwise noted. HOOKER Headers have not received an exemption from these code sections and are to legal for sale or use in California on vehicles originally equipped with catalytic converters, it is illegal, except for racing vehicles, which may never be driven upon a highway. To remove or otherwise render inoperative any emission control device on the regulated motor vehicles – check catalog listings to ensure proper application in the other 49 states, unless otherwise noted, HOOKER Headers are not legal for pollution-controlled motor vehicles, except for racing vehicles, which may never be used upon a highway and are not intended or applicable for highway use.

**16764HKR-INST**

**Date: 10-27-04**