

American Fabricating Co. 977 Hyrock Blvd, Boonville, IN 800-632-2320 www.AFCOracing.com

BILLET FAN SPACER

P/N 80191, 80192, 80193, 80194

For use with 3/4" and 5/8" water pump shafts

Please read the complete instructions before attempting installation.

Measure the water pump shaft at the hub to determine if it is $\frac{3}{4}$ " or $\frac{5}{8}$ ". If the pump's shaft measures $\frac{3}{4}$ " in OD install the fan spacer without the use of the steel reducer bushing. If the water pump's shaft is $\frac{5}{8}$ " press the $\frac{5}{8}$ steel bushing into the fan spacer so that it is flush with the opening.

Tighten fan mount bolts equally in a cris-cross pattern according to water pump manufacturers torque specification. Be certain that the supplied bolts do not contact the water pump housing behind the water pump hub or serious damage can result.

Contains: 1 Billet Fan Spacer, 4 Bolts, 4 Flat Washers, 4 Lock Washers, 1 Reducer Bushing

LIT-704 REV- 9/23/2008



American Fabricating Co. 977 Hyrock Blvd, Boonville, IN 800-632-2320 www.AFCOracing.com

BILLET FAN SPACER

P/N 80191, 80192, 80193, 80194

For use with 3/4" and 5/8" water pump shafts

Please read the complete instructions before attempting installation.

Measure the water pump shaft at the hub to determine if it is $\frac{3}{4}$ " or $\frac{5}{8}$ ". If the pump's shaft measures $\frac{3}{4}$ " in OD install the fan spacer without the use of the steel reducer bushing. If the water pump's shaft is $\frac{5}{8}$ " press the $\frac{5}{8}$ steel bushing into the fan spacer so that it is flush with the opening.

Tighten fan mount bolts equally in a cris-cross pattern according to water pump manufacturers torque specification. Be certain that the supplied bolts do not contact the water pump housing behind the water pump hub or serious damage can result.

Contains: 1 Billet Fan Spacer, 4 Bolts, 4 Flat Washers, 4 Lock Washers, 1 Reducer Bushing

LIT-704 REV- 9/23/2008