



509 Hemlock St
Philipsburg, PA 16866
Ph- 814.343.6315 Fax- 814.343.6318

Installation Instructions

support@umiperformance.com
www.umiperformance.com

78-88 GM G-Body hub assembly Item # 3047

IMPORTANT NOTES

The UMI 3047 hub assembly is designed to offer a high quality face-mount hub and bearing kit to the C5 retrofit G-body customer.

UMI is not responsible for fitment issues when using other companies' caliper mounts or other auxiliary components.

Please follow all applicable safety practices when working on a raised vehicle such as proper use of jack stands and safety glasses, and care when lifting heavy object such as the rear axle.

Technical specs:

5 x 4-1/2 and 5 x 4-3/4 bolt patterns

Requires 1/2-20 wheels studs with length chosen to fit your particular wheel

Bearings included

Installation Instructions:

1. The bearing cups are pre-installed in the Wilwood hub.
2. Clean thoroughly to remove any packing dust. You can wipe with WD-40 or equivalent.
3. Grease the inner bearing cone using a high quality synthetic. Pack tightly but do not over grease.
4. Lay greased bearing cone into cup.
5. Install seal. Lip should face inward to prevent grease loss.
6. Lube face of seal.
7. Grease outer bearing and place in hub.
8. Apply hub to spindle.
9. Install captive washer and nut.
10. Trim cotter pin so it fits inside cap.
11. Tighten until no play is felt then apply cotter pin on next hole. Do not under or over tighten.
12. Apply hubcap and screw on. Take care not to damage aluminum on aluminum threads.
13. Wheel studs can be retained with thread locking compound like Blue Loctite 242.

Item # 3047

78-88 GM G-body Hub Assembly
UMI Performance, Inc.
Manufactured in Philipsburg, PA-USA

Thank you for Putting Your Trust in A UMI Performance Product!

www.umiperformance.com