



THE ABSOLUTE LEADER IN VALVE TRAIN TECHNOLOGY

Description

Part Number:	12-268-4	Grind Number:	XE268H
Lifter Type:	Hydraulic Lifter	Engine Family:	Chevrolet 262-400 c.i. 8 Cyl. 1955-
Description:	Hydraulic-Best cam for modified 350		
Cam Family:	XTREME Energy™ Hydraulic Flat		

Specifications

	Intake	Exhaust
RPM-Range:	1800 to 5800	
Valve Lash:	Hyd.	Hyd.
Valve Timing:	0.006	
Duration:	268	280
Lobe-Center Angle:	114	230
Duration @ .050" Lift:	224	230
Valve Lift:		
Intake Centerline:	110	
Valve Lift:	0.477	0.48
Lobe Lift:	0.318	0.32

Installation Notes

[7] Stock springs cannot be used.

Valve Timing @ 0.006" Lift:

	Open		Close
Intake	22	BTDC	65
			ABDC
Exhaust	76	BBDC	23
			ATDC

Recommended Components

Complete K-Kit	Cam, Lifter & Gear GK-Kit	Small SK-Kit	Cam & Lifter CL-Kit
K12-268-4	N/A	SK12-268-4 [7]	CL12-268-4 [7]
Rocker, Push Rod RP-Kit	Lifter Kit	Timing Set	Gear Drive
RP1412-16 RPM1301-16	812-16 858-16	2100 3100	N/A
Rocker Arms	Push Rods	Valve Springs	Retainers
1412-16 [15,52] 1301-16 [15,52]	7812-16 7372-16	981-16 986-16 [2]	742-16 740-16 [3]
Valve Locks	Valve Seals	Lash Caps	Rev Kit
601-16 613-16	501-16 503-16 [2]	N/A	N/A
Distributor Gears	Stud Girdle	RPM kit	Spring Locator
N/A	N/A	N/A	N/A
Cam Phaser Limiter Kit	Spring Seats	Camshaft Break-In Lube	
N/A	N/A	159	

