

Description

Part Number:

12-675-4

Grind Number:

XS262S

Lifter Type:

Solid Lifter

Engine Family:

Chevrolet 262-400 c.i. 8 Cyl. 1955-

Description:

Solid-Excellent response, good mid-

Cam Family:

XTREME Energy™ Mechanical Flat



THE ABSOLUTE LEADER IN VALVE TRAIN TECHNOLOGY

Specifications

RPM Range:

1300 to 5800

Valve Timing:

0.015

Lobe-Center Angle:

110

Intake Centerline:

106

Valve Lash:

0.016

Duration:

262

Duration @ .050" Lift:

224

Valve Lift:

0.477

Lobe Lift:

0.318

Intake

0.016

262

224

0.477

0.318

Exhaust

0.016

268

230

0.488

0.325

Installation Notes

[7] Stock springs cannot be used.

Valve Timing @ 0.015" Lift:

Open

Close

Intake

25

BTDC

57

ABDC

Exhaust

68

BBDC

20

ATDC

Recommended Components

Complete K-Kit

Cam, Lifter & Gear GK-Kit

Small SK-Kit

Cam & Lifter CL-Kit

K12-675-4

N/A

SK12-675-4 [7]

CL12-675-4 [7]

Rocker, Push Rod RP-Kit

Lifter Kit

Timing Set

Gear Drive

RPM1412-16
RPM1301-16

813-16
800-16

2100
3100

N/A

Rocker Arms

Push Rods

Valve Springs

Retainers

1412-16 [15,52]
1301-16 [15,52]

7372-16
7972-16

981-16
986-16 [2]

742-16
740-16 [3]

Valve Locks

Valve Seals

Lash Caps

Rev Kit

601-16
613-16

501-16
503-16 [2]

N/A

N/A

Distributor Gears

Stud Girdle

RPM kit

Spring Locator

N/A

N/A

N/A

N/A

Cam Phaser Limiter Kit

Spring Seats

Camshaft Break-In Lube

N/A

N/A

159

