



THE ABSOLUTE LEADER IN VALVE TRAIN TECHNOLOGY

Description

Part Number:	12-676-4	Grind Number:	XS268S
Lifter Type:	Solid Lifter	Engine Family:	Chevrolet 262-400 c.i. 8 Cyl. 1955-
Description:	Solid-Great for street machines,		
Cam Family:	XTREME Energy™ Mechanical Flat		

Specifications

	Intake	Exhaust
RPM-Range:	1600 to 6000	
Valve Lash:	0.016	0.016
Valve Timing:	0.015	
Duration:	268	274
Lobe-Center Angle:	110	
Duration @ .050" Lift:	230	236
Intake Centerline:	106	
Valve Lift:	0.488	0.501
Lobe Lift:	0.326	0.335

Installation Notes

[7] Stock springs cannot be used.

Valve Timing @ 0.015" Lift:

	Open	Close
Intake	28 BTDC	60 ABDC
Exhaust	71 BBDC	23 ATDC

Recommended Components

Complete K-Kit	Cam, Lifter & Gear GK-Kit	Small SK-Kit	Cam & Lifter CL-Kit
K12-676-4	N/A	SK12-676-4 [7]	CL12-676-4 [7]
Rocker, Push Rod RP-Kit	Lifter Kit	Timing Set	Gear Drive
RPM1412-16 RPM1301-16	813-16 800-16	2100 3100	N/A
Rocker Arms	Push Rods	Valve Springs	Retainers
1412-16 [15,52] 1301-16 [15,52]	7372-16 7972-16	986-16 [2] 987-16	740-16 [3] 730-16
Valve Locks	Valve Seals	Lash Caps	Rev Kit
611-16 613-16	503-16 [2]	N/A	N/A
Distributor Gears	Stud Girdle	RPM kit	Spring Locator
N/A	N/A	N/A	N/A
Cam Phaser Limiter Kit	Spring Seats	Camshaft Break-In Lube	
N/A	N/A	159	

