

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to  
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT 3X Paint Stripper  
IDENTITY: Liquid Paint Stripper

Revision Date: 05/06/2010

-----

Section I

-----

|           |                       |                        |
|-----------|-----------------------|------------------------|
| Supplier: | DirectLine Industries | Telephone Numbers:     |
| Address:  | PO Box 15133          | Emergency 800-255-3924 |
|           | St. Louis             |                        |
|           | Missouri              | Information:           |
|           | Zip 63110             | 866-773-6136           |

-----

HMIS CODES: REACTIVITY: 0 FLAMMABILITY: 1 HEALTH: 3 PERSONAL PROTECT: X

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the  
ingredients contained in this product are listed on the TSCA inventory.)

=====

| Name               |    | Cas No. | OSHA PEL | ACGIH TLV | OTHER LIM | %     |
|--------------------|----|---------|----------|-----------|-----------|-------|
| METHYL ALCOHOL     | *  | 67-56-1 | 200 PPM  | 200 PPM   | N/A       | _____ |
| METHYLENE CHLORIDE | *+ | 75-09-2 | 25 ppm   | 50 ppm    | N/A       | _____ |
| _____              |    | _____   | _____    | _____     | _____     | _____ |
| _____              |    | _____   | _____    | _____     | _____     | _____ |
| _____              |    | _____   | _____    | _____     | _____     | _____ |
| _____              |    | _____   | _____    | _____     | _____     | _____ |
| _____              |    | _____   | _____    | _____     | _____     | _____ |
| _____              |    | _____   | _____    | _____     | _____     | _____ |

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT  
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING  
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

THIS PRODUCT CONTAINS CHEMICAL(S) MARKED WITH A + KNOWN  
TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

=====

|                       |   |                            |      |
|-----------------------|---|----------------------------|------|
| Boiling Point:        | >104 F  | Specific Gravity (water=1) | 1.20 |
| Vapor Pressure(mm Hg) | >100  | Melting Point:             | N/A  |
| Vapor Density(AIR=1)  | >1  | Evaporation Rate:          | >2   |
| Solubility in Water:  | EMULS   | (Butyl Acetate=1)          |      |
| Appearance and Odor:  | VISCOUS, HAZY LIQUID, STRONG CHLORINATED SOLVENT ODOR |                            |      |

Section IV: FIRE AND EXPLOSION HAZARD DATA

=====

Flash Point(Method Used):NONE      Flammable Limits: LEL:N/A      UEL: N/A  
Extinguishing Media: CO2, FOAM, DRY CHEMICAL, WATER SPRAY FOR COOLING.  
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS  
COMBUSTION BY PRODUCTS INCLUDE PHOSGENE AND HYDROGEN CHLORIDE GASES.

Unusual Fire and Explosion Hazards: MAY DEVELOP A FLAMMABLE ATMOSPHERE IN  
CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT 3X Paint Stripper

Stability: Unstable: Conditions to avoid: HOT SURFACES,  
Stable: X EXPOSURE TO TEMPERATURES ABOVE 100 F  
Incompatibility (Materials to Avoid): SOME PLASTICS, PAINTED SURFACES,  
RUBBER, NITRIC ACID, CHEMICALLY ACTIVE METALS.  
Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY  
PRODUCE PHOSGENE, OXIDES OF CARBON, AND HYDROGEN CHLORIDE GASES.  
Hazardous Polymerization: May Occur: Will Not Occur: X  
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards (Acute and Chronic):  
INHALATION: DIZZINESS. EXCESSIVE EXPOSURE MAY CAUSE UNCONSCIOUSNESS. EYES:  
IRRITATION, REDDENING. TEMPORAL EYE DAMAGE. SKIN: IRRITATION, ABSORBED,  
MAY CAUSE BURNS IF LEFT ON SKIN. INGESTION: MAY CAUSE IRRITATION AND BURNING  
Carcinogenicity: NTP: Yes IARC Monographs: Yes OSHA Reg: Yes  
Signs and Symptoms of Exposure: HEADACHE, MENTAL CONFUSION, DEPRESSION,  
LIVER EFFECTS, BRONCHITIS, NAUSEA, LACK OF BALANCE, VISUAL DISTURBANCES.

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE  
WILL AGGRAVATE RESPIRATORY, PULMONARY OR CARDIOVASCULAR ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. CPR IF  
NEEDED. CONSULT PHYSICIAN. EYES: FLUSH EYES WITH WATER FOR 15 MIN. CONSULT  
PHYSICIAN. SKIN: WASH WITH SOAP & WATER. CONSULT PHYSICIAN. INGESTION: DO NOT  
INDUCE VOMITING WITHOUT CONSULTING DOCTOR OR POISON CONTROL. GIVE WATER.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: CONTAIN SPILL.  
PRODUCT WILL UNDERGO RAPID EVAPORATION. VENTILATE AREA. USE PROPER PPE.  
RESIDUE SHOULD BE COVERED WITH AN ABSORBENT CLAY MATERIAL AND PLACED IN  
DRUMS FOR DISPOSAL.  
Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE  
AND LOCAL GUIDELINES. OFFER DRUMS FOR RECYCLING. DO NOT REUSE EMPTY CON-  
TAINER. SMALLER CONTAINERS SHOULD BE RINSED AND PLACED IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: STORE IN A COOL, DRY AREA.  
KEEP AWAY FROM HEAT AND OPEN FLAMES. KEEP CONTAINERS TIGHTLY SEALED.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.  
WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT WHEN USING THIS PRODUCT.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE IN WELL VENTILATED AREA  
Ventilation: Local Exhaust: ADEQUATE  
Mechanical: N/A Special: N/A  
Other: N/A  
Protective Gloves: GLOVES SHOULD BE A FLOURSILICONE OR A FLOUR ELASTOMER  
Eye Protection: SAFETY GOGGLES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.  
Other Protective Clothing or Equipment:  
LONG SLEEVE CLOTHING- TO COVER SKIN  
Work/Hygienic Practices:  
WASH HANDS AFTER USE