

INSTRUCTION

910-31902 Non-Emergency Brake


910-31921 Emergency Brake

©Speedway Motors, Inc. 2015

CAR REAR DISC BRAKE CONVERSION (PRESSED BEARING STYLE)

PARTS LIST


- (2) New rotors
- (2) 2 piece brackets
- (8) 5/16 spacers (4)
1/8 spacers (2)
Spacer plates
- (8) 3/8-24 x 1 1/2 Grade 8 bolts
- (8) 3/8-24 x 2 Grade 8 bolts
- (16) 3/8 flat washers
- (16) 3/8 grade 8 nuts



REPLACEMENT AND ADDITIONAL PARTS


- (2) 1978-83 Chevelle, Monte Carlo, El Camino, Malibu, Tempest, Cutlass, F-85, Pontiac Grand Prix, Le Mans, GTO, Grand Am, Bonneville front calipers (no parking brake) with pads and mounting screws.
- (2) 1979-85 El Dorado, Riviera, Toronado, 1980-85 Seville with emergency brakes on the calipers. Rear calipers with parking brakes, pads and mounting screws.

INSTALLATION INSTRUCTIONS



1. Installation must begin by taking the axles out of the housing. Start by installing the t-bolts into the housing flange. The spacer plate can then be installed on the end


of the housing as shown. Next, insert the axle and bearing into the housing.




2. Install the base bracket between the spacer and the retainer and secure using the supplied nuts. The ears on the base bracket should be positioned so they will mount the caliper up toward the rear as shown.



3. Make sure to use a quality brake cleaner and rag to clean the anti-corrosion coating off your brake rotors before installing them. This coating can contaminate brake pads.




4. Install the rotor over the axle studs and temporarily secure using two hand-tightened lug nuts.




5. Insert the brake pads in the caliper and install the caliper brackets as shown using the supplied Allen-head slider bolts.




6. Test fit the caliper on the rotor, making sure the bleed screw is facing up. Your brake kit comes with bracket spacers in two different thicknesses. Determine the number and thickness of spacers required to properly position the caliper in relation to the rotor.




7. Remove rotor and bolt the caliper bracket to the base bracket using the spacer(s) determined in the previous step.



8. Re-install rotor, again using two lug nuts to hold it in place.



9. Install caliper on bracket using supplied Allen-head slider bolts.



10. With caliper installed, double check to verify the gap between the brake pads and rotors is equal on both sides. Adjust shim packs as needed to achieve equal gap.



11. Since this brake kit uses floating calipers that move with normal brake wear and operation, it is critical to use a flexible brake line between the caliper and axle housing. A tab should be welded to the housing to support the junction between the flex line and hard line.


INSTRUCTION

910-31046

©Speedway Motors, Inc. 2015


ADJUSTING AND BLEEDING EMERGENCY BRAKE CALIPERS

1. When you install the calipers, put them in the position you like, one where the cable will work well (if you have the park brake calipers) and the hose connection is in a good location. If you go off road you can mount the calipers high to avoid brush and rocks. Don't worry about being in the right position to bleed the brakes. The calipers have to be taken off the brackets to bleed anyway, and once they are bled it does not matter what position they are in.
2. Once everything is installed and before you put the wheels on, bleed the calipers. Air rises so the bleed screw must be at the top. You can start by using the normal bleeding methods, but the brakes will not work properly and you will have a soft pedal if you do not take the calipers off of the brackets and gravity bleed them to get the last of the air out.
3. To gravity bleed, remove the master cylinder cover, take the caliper off of the bracket and hold behind the axle. Hold the caliper so that the bleed screw points forward, horizontal with the ground on the (small) 5^{1/2}-inch pin-to-pin calipers and straight up on the (large) 7-inch pin-to-pin calipers. The mounting holes in the ears are around 45° on a non-parking-brake caliper and straight up (one hole above the other) on a parking brake caliper. Open the bleed screw and the fluid will start to dribble out. Slowly move the calipers just in case you are not in the correct position and also tap on the calipers with a rubber hammer to knock bubbles loose. Once the fluid is clear with no air bubbles, close the bleeder and hang that caliper on a wire and do the other side. Do both calipers again and then reinstall. (Do not step on the hydraulic pedal yet.) Go to step 5 for non-parking brake calipers.
4. Adjust the parking brake levers by pushing them forward. Each time you push them they should move off of the stop 3/8 to 1/2 inch. When released, they should always return to the stop. If they will not adjust, try putting a lever between the rotor and the pad and putting pressure on the piston. Now push the lever, releasing pressure on the pad as the caliper adjusts. These are the only two ways we know of to adjust the parking brake. If the calipers won't adjust, you will have a low pedal because the piston will retract too far and will use



up all your hydraulic pedal travel to put the brakes on. Once the parking brake calipers are adjusted, put a c-clamp on between the lever and the bracket to hold the parking brakes locked up.

5. Step on the hydraulic pedal. It should be high and hard. If it is low and spongy or it will pump up, you still have air. Take the caliper off the brackets and bleed some more. If you have parking brake calipers and they are locked up against the rotors and there is no air in the rear system, then there will be no fluid movement in the rear brake system and the pedal should be as high as before you changed the brakes and had the parking brake on. It does not matter what size master cylinder you have. If there is no fluid movement you will have a high and hard hydraulic pedal. There might be a problem with your front system since you have a dual braking system. But if you have not changed the front, your pedal should be high and hard. It is not as easy to check if you are using non-parking brake calipers. The calipers run close to the rotors so check to see that the pads won't rattle. If your pedal is low and spongy, you have air. Remove the calipers and bleed them some more.



IMPORTANT

DISCLAIMER

In an effort to offer our customers the low prices, quick service and great value, Speedway Motors reserves the right to change suppliers, specifications, colors, prices, materials. Each of the previous items is subject to change without notice. Speedway is not responsible for any typographical errors or misinterpretations. Quantities are limited on some items.

WARRANTY DISCLAIMER

The purchaser understands and recognizes that racing parts, specialized street rod equipment, and all parts and services sold by Speedway Motors, Inc. are exposed to many and varied conditions due to the manner in which they are installed and used. Speedway Motors, Inc. makes no warranties, either express or implied, including any warranty of merchantability or fitness for a particular purpose other than those contained in its current catalog with respect to the goods identified on the face of the invoice. There is no warranty expressed or implied as to whether the goods sold hereby will protect purchaser or ultimate user of such goods from injury or death. Speedway Motors assumes no liability after this period.

BRAKE INSTALLATION ALERT

The selection and installation of brake components should only be done by personnel experienced in the proper installation and operation of braking systems. The installer must use his/her own discretion to determine the suitability of all brake components and brake kits for every particular application. Speedway Motors, Inc. makes no warranties either expressed or implied including any warranty of merchantability or fitness for a particular purpose, other than those contained in its current catalog or website with respect to the goods identified on the face of the invoice, There is no warranty expressed or implied as to whether the goods sold hereby will protect the purchaser or ultimate user of such goods from injury or death.

DAMAGE CLAIMS

Always inspect your package upon delivery. Inspect all packages in the presence of the delivery driver. The driver must note any damage. Ask the driver the Carrier's procedures for handling damage claims. You must hold the original box, packing material and damaged merchandise for inspection or the carrier will not honor the claim. Notify Speedway Motors customer service department for instructions on returning damaged goods. Speedway is not responsible if no notification is given within 5 days of receipt.

SHORTAGES

Always check the contents of your delivery to insure all the parts that you ordered were received. Please read the invoice. Double check all packing materials, small items may be wrapped inside with these products. Shortages may occur from damage to the box, so save all packing materials. Inspect the box for holes that would allow parts to fall out. If you are missing any item(s) be sure to check your invoice for back orders or canceled items before calling the customer service department. If Speedway has to split a shipment into multiple boxes, packages may be delivered on different days. You need to contact the customer service department within 5 days of delivery to assure the prompt replacement. Speedway Motors assumes no liability after this period.

REFUSALS

All refused COD customers will be billed a 15% restocking charge plus freight to and from the destination! If you have questions please contact Speedway's customer service department.

WARRANTY CLAIMS

If an item has a manufacturer's warranty as being free from defects we will exchange only. If the item has been used and you are requesting warranty work, this may take up to 30 days as warranty work is done by the manufacturer NOT Speedway Motors. If you have any questions please contact customer service.

RETURNS

Speedway wants you to be satisfied with your purchase. If within 30 days after you receive your shipment you are not satisfied, you may return the item for refund or exchange. All exchanged or returned merchandise must be in original factory condition with no modifications or alterations. Returned merchandise must include all packaging materials, warranty cards, manuals, and accessories. If the items being returned need to be repackaged there will be a re-packing charge. Re-pack the item in a sturdy box and include a copy of your invoice and complete the form on the back of the invoice. You must ship orders back **PRE-PAID. WE DO NOT ACCEPT COD SHIPMENTS.** All exchanges need to have reshipping charges included. Items that are returned after 30 days are subject to 15% restocking charges. All fiberglass returned will have 15% restocking charge. No returns on electrical parts, video tapes, and books. Absolutely no returns on special order or close out merchandise.

FREE CATALOGS

Speedway Motors offers FREE catalogs for Race, Street, Sprint and Midget, Sport Compact and Pedal Car Restoration.

Some items are not legal for sale or use in California on pollution controlled motor vehicles. These items are legal in California for racing vehicles only which may never be used upon a highway.

**Speedway Motors Inc.,
P.O. Box 81906 Lincoln, NE 68501
800.979.0122 SpeedwayMotors.com**

