

THIS IS A QUICK GUIDE FOR FLUID TYPES AND HOSE ENDS, ALL OTHER INFORMATION IS IN THE CATALOG INCLUDING FITTING DIMENSIONS (LOCATED IN THE TECHNICAL SECTION).

| FLUID/AIR TYPE | | | | | | | | | | | |
|----------------|----------|----------|------|------|--------|-----------|---------|-------|-------|-------|--------|
| HOSE | PUMP GAS | RACE GAS | ALKY | E85 | DIESEL | BIO-FUELS | COOLANT | ATF | OIL | BRAKE | VACUUM |
| Perform-O-Flex | ● ** | ● | ● | ● ** | ● | | ● | ● | ● | | ● |
| Auto-Flex | ● ** | ● | ● | ● ** | ● | | ● | ● | ● | | ● |
| Pro-Lite 350 | ● ** | ● | ● | ● ** | ● | | ● | ● | ● | | ● * |
| Pro-Lite Ultra | ● ** | ● | ● | ● ** | ● | | ● | ● | ● | | ● |
| Super Stock | ● ** | ● | ● | ● ** | ● | | ● | ● *** | ● *** | | ● * |
| Speed-Flex | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Ultra-Flex | ● | ● | ● | ● | ● | ● | ● | ● | ● | | ● |

* Inner support spring might be needed for high vacuum or tight bends (Page 105)

** Compatibility with 2011 reformulated liner

*** Under 250F degrees

| HOSE ENDS | | | | | | | | | | | |
|--------------------------|-------------|-------------|----------|------------|-----------|------------|-------------|------------|------------|----------------|--|
| HOSE | HOSE SERIES | SWIVEL-SEAL | AUTO-FIT | AUTO-CRIMP | AUTO-MATE | ECON-O-FIT | SUPER STOCK | SPEED-SEAL | ULTRA-FLEX | POWER STEERING | |
| PERFORM-O-FLEX | 4 | ● | ● | ● | ● | ● | | | | | |
| AUTO-FLEX | 3 | ● | ● | ● | ● | ● | | | | | |
| PRO-LITE 350 | 35 | ● | ● | ● | ● | ● | | | | | |
| PRO-LITE ULTRA | 39 | ● | ● | ● | ● | ● | | | | | |
| SUPER STOCK - BLACK/BLUE | 78/79 | | | | | ● | ● | | | | |
| SPEED-FLEX | 6 | | | | | | | ● | | | |
| ULTRA-FLEX - KEVLAR/S.S. | 65/66 | | | | | | | | ● | | |
| POWER STEERING HOSE | 13 | | | | | | | | | ● | |

| | | HOSE ENDS | | Same fitting (pair with either Collar or Clamp) | | | | | | |
|---------------------------|--|-------------|----------------------|---|------------|---------------|------------|--------------|------------|-------------|
| HOSE END CHARACTERISTICS | | SWIVEL-SEAL | AUTO-FIT | AUTO-CRIMP | AUTO-MATE | SUPER STOCK | SPEED-SEAL | ULTRA-FLEX | ECON-O-FIT | P/S |
| Fitting to Hose Mate Type | | Cutter | Compression | Crimp Collar | Band Clamp | Crimp Collar* | Olive | Crimp Collar | Band Clamp | Compression |
| Reusability | | YES | YES | YES** | YES | YES** | YES | YES** | YES | YES |
| Adjustability/Swivel | | YES | NO | NO | N/A | NO | YES/NO | NO | N/A | NO |
| Hose End Series | | 8 | 3 (Alum.) & 4 (S.S.) | 7 | 7 | 7 | 6 | 67 | 90 | 13 |

* Can be used with collar un-crimped on low pressure applications. Collar should be crimped to assure 250 PSI capability (reference on bottom right P. 115)

** Reusable with replacement collar see - Auto-Crimp Page 19 / Super Stock Page 22

| HOSE END PART NUMBER PREFIX | | PREFIX |
|-----------------------------|--|--------|
| Red/Blue Anodized | | None |
| ANO-TUFF Black Hard Coat | | AT |
| Unanodized - Polished | | UP |

(All page number references are to the 2011 Catalog)