



Part Number 57-0360 INSTALLATION INSTRUCTIONS

Toyota Corolla L4 1.6L 16v 110bhp 1997-2000

1. Carefully remove the air temp sensor from the side of the air box lid. (Fig. 1)
2. Unclip & remove the intake hose from the air box lid. (Fig. 2)
3. Unclip & remove the air box lid from the base, remove the lid from the vehicle. (Fig. 3)
4. Remove the 3 bolts securing the air box base to the inner wing. (Fig. 4)
5. Remove the air box base from the pick-up pipe & carefully lift the base from the vehicle. (Fig. 5)
6. Fit the new bracket to the rear threaded hole located on the air box mounting support frame using the original bolt. (Fig. 6)
7. Fit the metal adapter tube up to the lip in the Air filter base & secure with the #44 hose clip supplied. Fit the Air filter assembly onto the original intake hose & secure with the original hose clip. (Fig. 7)
8. Attach the studded lid of the Air filter to the hole in the mounting bracket & secure using the nylock nut, flat washer & spacer supplied. (Fig. 8)
9. Insert the air temp sensor into the hole in the base of the Air filter. (Fig. 9)
10. Carefully lengthen the flexi cold air hose, feed the hose down to the under-tray. Secure the top of the flexi hose to the battery cable using a plastic tie supplied. Position the cold air hose to finish approx. 10cm / 4" from the Air filter. (Fig.10)
11. Taking all necessary safety precautions as per manufacturers instructions, raise the front of the vehicle. Cut a 65mm diameter hole in the under tray as shown. Feed the flexi cold air hose through the hole & secure the hose to the under tray using a plastic tie supplied. (Fig.11)
12. Installation is now complete.

Parts list:

- 1 x Air filter element.
- 1 x #44 Hose Clip.(filter)
- 1 x Mounting Bracket.
- 1 x Flexi Cold Air Hose.
- 2 x Moulded Plastic Sleeves.
- 1 x Literature Pack.
- 1 x Fixing Kit :-
 - 1 x Nylock Nut.
 - 1 x Metal Flat Washer.
 - 2 x Plastic Cable Ties.
 - 1 x Filter Spacer.
 - 1 x Metal Adapter Tube.

WARNING: Before starting the engine carry out a final fitment check of the K&N performance kit. It will be necessary for all intake systems to be checked periodically for realignment, clearance and tightening of all connections. Failure to follow the above instructions or proper maintenance may void the warranty.

FILTER MAINTENANCE: K&N suggests checking the filter periodically for excessive dirt build-up. When the element becomes covered in dirt (or once a year), service it according to the instructions on the Recharger service kit available from your K&N dealer, part number 99- 5003EU.

For cleaning instructions please visit our website: www.knfilters.com/cleaning



Fig. # 1



Fig. # 2



Fig. # 3



Fig. # 4



Fig. # 5



Fig. # 6



Fig. # 7



Fig. # 8




Fig. # 9



Fig. # 10



Fig. # 11

For technical support contact our European technical team: "eindhoven.tech@knfilters.com" We will try to answer your mail within 48 hours.

For UK technical enquiries contact R&D department at 01925-636950, Mon-Thu from 8:30 am to 5 pm.

For other K&N products and / or more information about the K&N products please visit our website: www.knfilters.com