



INSTALLATION INSTRUCTIONS

Part Number E-4505

This filter fits: **See current catalog for applications**

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter money can buy. With proper care this air filter can last many seasons. This air filter is a direct replacement for the stock air filter and no modifications will be required. However, the following procedure MUST be followed to ensure a proper fit and seal of the air filter.

1. Remove the air cleaner cover and remove the stock air filter.
2. Install the provided top plate onto the K&N Filtercharger.
3. Install the K&N Filtercharger onto the air cleaner base.
4. Install the provided rubber washers onto the stock stud.
5. Reinstall the stock air cleaner cover and tighten the stock screw.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.

• 1455 CITRUS ST., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 951-826-4001
• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17443a
01/22/07



INSTALLATION INSTRUCTIONS

Part Number E-4505

This filter fits: **See current catalog for applications**

FREE K&N DECAL** To register your warranty, please see us online at knfilters.com/register. **FREE K&N DECAL

Congratulations, you have purchased the finest air filter money can buy. With proper care this air filter can last many seasons. This air filter is a direct replacement for the stock air filter and no modifications will be required. However, the following procedure MUST be followed to ensure a proper fit and seal of the air filter..

1. Remove the air cleaner cover and remove the stock air filter.
2. Install the provided top plate onto the K&N Filtercharger.
3. Install the K&N Filtercharger onto the air cleaner base.
4. Install the provided rubber washers onto the stock stud.
5. Reinstall the stock air cleaner cover and tighten the stock screw.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.

• 1455 CITRUS ST., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 951-826-4001
• e-mail: tech@knfilters.com • WWW: <http://www.knfilters.com>

17443a
01/22/07