



# INSTALLATION INSTRUCTIONS

## Part Number: HA-1110

This filter fits: See catalog for current applications

\* FREE K&N® decal To register your warranty, please see us online at [knfilters.com/register](http://knfilters.com/register). FREE K&N® decal \*

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modification will be required. However the following procedures MUST be followed to ensure the proper fit and seal of the K&N® air filter.

### INSTALLATION:

1. Remove the O.E. filter per service manual. Save the 2 holding screws from the O.E. filter, they will be used to install the K&N® air filter.
2. Place the K&N® air filter onto the air box base with the K&N logo facing upward. The K&N® air filter will only fit one way (**Fig. 1**).
3. Slide the washers onto the screws, thread them through the air filter base plate holes and into the threaded holes of the air box base (**Fig. 2**).
4. Tighten down the screws until each screw firmly sandwiches the washer between it and the base plate (**Fig 3**).
5. Once the screws are tightened as described in step 4, tighten each screw 2 ½ turns.
6. Install the air box lid per service manual.

**THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.**



Fig. 1



Fig. 2



Fig. 3