



INSTALLATION INSTRUCTIONS

Part Number YA-1184

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

INSTALLATION

1. Remove the stock air filter.
2. Discard the stock air filter retaining clips, they will not be reinstalled.
3. Oil the K&N Filtercharger® with the provided oil pillow packs.
4. Install the K&N Filtercharger® into the air box.

Note: The tab on the K&N Filtercharger® will fit into the slot in the air box.

5. Install the provided locating bar into the air box by inserting the legs into the channels where the stock air filter retaining clips were mounted.

Note: When properly installed the bar will contact the hard rubber on the outside of the K&N Filtercharger®.

CAUTION: The bar must not touch the wire mesh of the K&N Filtercharger®. If it does, the bar is not properly installed and will cause damage to the K&N Filtercharger®.

6. Reinstall the side cover.

Note: The tab on the K&N Filtercharger® will fit into the slot on the side cover.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.