



INSTALLATION INSTRUCTIONS

PART NUMBER: YA-2588

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

* **FREE K&N® decal** To register your warranty, please see us online at knfilters.com/register. **FREE K&N® decal ***

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter is a direct replacement for the stock air filter, and no modification will be required. However the following procedures **MUST** be followed to ensure the proper fit and seal of the K&N® air filter.

INSTALLATION:

1. Remove the stock air filter according to the service manual.

NOTE: OE washer and wing nut will be reused in step 4.

2. Wipe away any dirt and dust from the inside of the air filter housing. (Fig. 1)

NOTE: A damp cloth can be used to clean the inside of the air filter housing.

3. Install the K&N® air filter into the airbox base and align the hole in the top of the filter with the stud on the airbox base. (Fig. 2)

4. Once the K&N® air filter is properly installed in the airbox base, install the provided K&N® rubber washer onto the top of the filter followed by the OE washer and wing nut that was used for the replaced filter. (Fig. 3)

5. Reinstall air box lid per service manual.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3