



# INSTALLATION INSTRUCTIONS

## PART NUMBER: YA-6050

**This filter fits:**

SEE CATALOG FOR CURRENT APPLICATIONS

\* **FREE K&N® decal** To register your warranty, please see us online at [knfilters.com/register](http://knfilters.com/register). **FREE K&N® decal** \*

Congratulations, you have just purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

### INSTALLATION:

1. Remove the stock air filter. Keep the stock bolt that holds the air filter in place.
2. Apply the provided gasket to the open side of the K&N® air filter.
3. Cut the tip off the provided oil pillow pack.
4. Run the tip of the oil pillow pack along the edge of each pleat.

**NOTE: Use only 1/2 of the oil pillow pack. If the entire oil pillow pack is used the air filter will be over oiled.**

5. Apply a thin layer of the K&N® sealing grease. This will help the K&N® air filter slide into the airbox without tearing the gasket.
6. Install the K&N® air filter into the airbox, using the stock bolt.
7. Reinstall the side cover.

**THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.**