

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : Valvoline™ POWER STEERING FLUID

Product code : 602241

Manufacturer or supplier's details

Company name of supplier : Niteo Products,LLC

Address : Dallas TX 19162

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : POWER STEERING FLUID

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin irritation : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H361f Suspected of damaging fertility.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
PETROLEUM DISTILLATES	Not Assigned	>= 90 - < 100
TRICRESYL PHOSPHATE	1330-78-5	>= 0.1 - < 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Move to fresh air. Consult a physician after significant exposure. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If on clothes, remove clothes. Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. Wash contaminated clothing before re-use.

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

If skin irritation persists, call a physician.

- | | |
|---|---|
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing. |
| If swallowed | : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : Causes skin irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility. |
-

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---|--|
| Suitable extinguishing media | : Water spray
Carbon dioxide (CO2) |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Specific extinguishing methods | : Product is compatible with standard fire-fighting agents. |
| Further information | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for firefighters | : In the event of fire, wear self-contained breathing apparatus. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform |
-

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Components	CAS-No.
PETROLEUM DISTILLATES	Not Assigned
TRICRESYL PHOSPHATE	1330-78-5

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be dis-

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

cussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Odour	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 1.33 hPaThe value is calculated
Density	: No data available
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity Viscosity, dynamic	: No data available

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

Viscosity, kinematic	: 42 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Hazardous polymerisation does not occur.
Conditions to avoid	: Heat No data available
Incompatible materials	: Strong oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact

Acute toxicity

Not classified based on available information.

Components:**TRICRESYL PHOSPHATE:**

Acute oral toxicity	: LD50 (Rat, male and female): > 20,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat, male and female): > 11.1 mg/l Exposure time: 1 h Test atmosphere: dust/mist Assessment: The component/mixture is minimally toxic after short term inhalation. Remarks: No mortality observed at this dose.
Acute dermal toxicity	: LD50 (Rabbit, male and female): 3,700 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:**PETROLEUM DISTILLATES:**

Result: Skin irritation

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

TRICRESYL PHOSPHATE:

Species: Rabbit
Exposure time: 4 h
Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: No eye irritation

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**TRICRESYL PHOSPHATE:**

Species: Rabbit
Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.
Respiratory sensitisation: Not classified based on available information.

Components:**TRICRESYL PHOSPHATE:**

Exposure routes: Dermal
Species: Mouse
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 429
GLP: yes

Germ cell mutagenicity

Not classified based on available information.

Components:**TRICRESYL PHOSPHATE:**

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Species: Chinese hamster lung cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative
	: Test Type: Ames test Species: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: negative

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

Valvoline™ POWER STEERING FLUID

Version 1.1	Revision Date: 07/10/2017	SDS Number: 600000000310	Date of last issue: 05/23/2016 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility.

Components:**TRICRESYL PHOSPHATE:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:**PETROLEUM DISTILLATES:**

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Component RQ (lbs)
TOLUENE	108-88-3	1000	1000
ETHYL ACRYLATE	140-88-5	1000	1000
LEAD	7439-92-1	10	10
BENZENE	71-43-2	10	10
ARSENIC	7440-38-2	1	1
LEAD	7439-92-1	10	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	07/10/2017	600000000310	05/23/2016
			Date of first issue: 05/23/2016

US State Regulations**Massachusetts Right To Know**

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

PETROLEUM DISTILLATES	Not Assigned
PROPRIETARY OF LUBRIZOL 7075f/7075	Not Assigned
NOT HAZARDOUS	
TOLUENE	108-88-3


California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.
WARNING! This product contains a chemical known to the State of California to cause cancer.
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	
FLAMMABILITY	
PHYSICAL HAZARD	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 07/10/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

Valvoline™ POWER STEERING FLUID

Version	Revision Date:	SDS Number:	Date of last issue: 05/23/2016
1.1	07/10/2017	600000000310	Date of first issue: 05/23/2016

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN