		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 07/14/2017
		Print Date: 12/7/2017
		SDS Number: R0173128
Valvoline™ VR1™ SAE 20W-50 Motor Oil		Version: 1.6
822347		

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION****Product identifier**

Trade name : Valvoline™ VR1™ SAE 20W-50  
Motor Oil

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825)	<b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)  <b>Regulatory Information Number</b> 1-800-TEAMVAL (1-800-8326-825)  <b>Product Information</b> 1-800-TEAMVAL (1-800-8326-825)
--	---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**GHS label elements**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Defatter

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
Mineral Oil		Asp. Tox. 1; H304	5.698
Lubricating oils (petroleum), hydrotreated	64742-58-1	This material is considered hazardous under the OSHA Hazard	1.8686



<b>SAFETY DATA SHEET</b>	Revision Date: 07/14/2017
	Print Date: 12/7/2017
	SDS Number: R0173128
Valvoline™ VR1™ SAE 20W-50 Motor Oil 822347	Version: 1.6

		Communication Standard criteria, based on hazard(s) not otherwise classified.	
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	Asp. Tox. 1; H304	1.1396

**SECTION 4. FIRST AID MEASURES**

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.  
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
acne  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)
- Notes to physician : No hazards which require special first aid measures.



**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO2)  
Dry chemical
  
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
  
- Hazardous combustion products : carbon dioxide and carbon monoxide  
Hydrocarbons  
nitrogen oxides (NOx)
  
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
  
- Further information : Standard procedure for chemical fires.
  
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
  
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
  
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
  
- Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.

**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lubricating oils (petroleum), hydrotreated	64742-58-1	TWA	5 mg/m3 Inhalable fraction	ACGIH
Distillates (Petroleum), Hydrotreated Heavy Paraffinic	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

**Hazardous components without workplace control parameters**

Components	CAS-No.
Mineral Oil	

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).

**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

Wear as appropriate:  
Safety shoes

Hygiene measures : General industrial hygiene practice.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	: liquid
Colour	: amber
Odour	: mild
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 600.01 °F / 315.56 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Gas
Flash point	: > 390 °F / > 199 °C Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 7 %(V) GLP: Calculated Explosive Limit
Lower explosion limit	: 0.9 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 0.1 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: 0.8880 (15.56 °C)
Density	: 0.8816 g/cm <sup>3</sup> (15.56 °C)
Solubility(ies) Water solubility	: negligible

**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Thermal decomposition : No data available
- Viscosity
- Viscosity, dynamic : No data available
- Viscosity, kinematic : 182 mm<sup>2</sup>/s (40 °C)
- Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

- Reactivity : No decomposition if stored and applied as directed.
- Chemical stability : Stable under recommended storage conditions.
- Possibility of hazardous reactions : Product will not undergo hazardous polymerization.
- Conditions to avoid : None known.
- Incompatible materials : Strong oxidizing agents
- Hazardous decomposition products : carbon dioxide and carbon monoxide  
Hydrocarbons  
Nitrogen oxides (NO<sub>x</sub>)

**SECTION 11. TOXICOLOGICAL INFORMATION**

- Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion


**Acute toxicity**

Not classified based on available information.

**Components:**

Lubricating oils (petroleum), hydrotreated:

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by ingestion under GHS.

		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 07/14/2017
		Print Date: 12/7/2017
		SDS Number: R0173128
Valvoline™ VR1™ SAE 20W-50 Motor Oil		Version: 1.6
822347		

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:  
 Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

Lubricating oils (petroleum), hydrotreated:  
 Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:  
 Result: Slight, transient irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

Lubricating oils (petroleum), hydrotreated:  
 Result: Slight, transient irritation

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:  
 Result: No eye irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
 Respiratory sensitisation: Not classified based on available information.  
 Germ cell mutagenicity  
 Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

**Components:**

Mineral Oil:

May be fatal if swallowed and enters airways.

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:**

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other aquatic invertebrates : LC50 (Brine shrimp (*Artemia salina*)): > 22,500 mg/l  
Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility

Distillates (Petroleum), Hydrotreated Heavy Paraffinic:

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l





**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------

**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------



**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act  
CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ZINC	7440-66-6	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.



**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313**

Zinc O,O,O',O'- tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate	2215-35-2	0.61 %
ZINC DIALKYL DITHIOPHOSPHATE	68649-42-3	0.47 %
PHOSPHORODITHIOIC ACID, MIXED O,O- BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS	84605-29-8	0.36 %

**California Prop 65** This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

**The components of this product are reported in the following inventories:**

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 07/14/2017

<b>NFPA:</b>	<b>HMIS III:</b>
--------------	------------------

**SAFETY DATA SHEET**

Revision Date: 07/14/2017


Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347



**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class III B

**Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline’s Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”



**SAFETY DATA SHEET**

Revision Date: 07/14/2017

Print Date: 12/7/2017

SDS Number: R0173128

Valvoline™ VR1™ SAE 20W-50 Motor Oil

Version: 1.6

822347

IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association  
NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency  
RTK : Right to Know  
WHMIS : Workplace Hazardous Materials Information System