

		Page: 1
SAFETY DATA SHEET		Revision Date: 07/21/2017
		Print Date: 12/7/2017
		SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil		Version: 2.0
VV981		

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier
Trade name : SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825) SDS@valvoline.com	Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-8326-825) Product Information 1-800-TEAMVAL (1-800-8326-825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification
Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

Chronic aquatic toxicity : Category 4

GHS label elements
Hazard pictograms : 

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.

	Page: 2
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil	Version: 2.0
VV981	

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
ORGANIC COMPOUND	151006-62-1	Aquatic Chronic 4; H413	>= 20.00 - < 30.00
PETROLEUM DISTILLATES	64742-55-8	Not a hazardous substance or mixture.	>= 10.00 - < 20.00
POLYMER	151006-63-2	Aquatic Chronic 4; H413	>= 10.00 - < 20.00
ORGANIC COMPOUND	68937-96-2	3; H316 Skin Sens. 1B; H317 Aquatic Acute 3; H402 Aquatic Chronic 3; H412	>= 1.00 - < 10.00
Mineral Oil		Asp. Tox. 1; H304	>= 1.00 - < 10.00

	Page: 3
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		Flam. Liq. 4; H227 Acute Tox. 4; H302 1; H318 Skin Sens. 1; H317 Aquatic Acute 2; H401 Aquatic Chronic 2; H411	>= 1.00 - < 10.00

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: Remove contaminated clothing. If irritation develops, get medical attention. If on skin, rinse well with water. First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. Wash contaminated clothing before re-use.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

	Page: 4
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

Most important symptoms and effects, both acute and delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
May cause an allergic skin reaction.
Causes serious eye irritation.

Notes to physician

: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : acrolein
Aldehydes
carbon dioxide and carbon monoxide
formaldehyde
Ketones
Hydrocarbons
Sulphur oxides
Nitrogen oxides (NO_x)
hydrogen sulfide

Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

	Page: 5
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil	Version: 2.0
VV981	

Product is compatible with standard fire-fighting agents.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

Revision Date: 07/21/2017

Print Date: 12/7/2017

SDS Number: R0388288

SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil

Version: 2.0

VV981

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
PETROLEUM DISTILLATES	8042-47-5	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA (Mist, inhalable)	5 mg/m3 Mist, inhalable	CR OEL
		STEL (Mist)	10 mg/m3 Mist	CR OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : Respiratory protection is not required under normal conditions of use.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

: Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

	Page: 7
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: amber
Odour	: mild
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 330 °C (1,013.333333 hPa) Calculated Phase Transition Liquid/Gas
Flash point	: > 199 °C Method: Cleveland open cup
Evaporation rate	: < 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 1.3333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	: > 1 AIR=1
Relative density	: No data available
Density	: 0.8603 g/cm ³ (15.6 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	

**SAFETY DATA SHEET**

Revision Date: 07/21/2017

Print Date: 12/7/2017

SDS Number: R0388288

SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil

Version: 2.0

VV981

Viscosity, dynamic : No data available

Viscosity, kinematic : 171 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Aldehydes
carbon dioxide and carbon monoxide
Hydrocarbons
hydrogen sulfide
Nitrogen oxides (NO_x)
Sodium oxides
Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**ORGANIC COMPOUND:**

Acute oral toxicity : LD₅₀ (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC₅₀ (Rat): > 5.06 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD₅₀ (Rat): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

POLYMER:Acute oral toxicity : LD₅₀ (Rat): > 5,000 mg/kg

SAFETY DATA SHEET

Revision Date: 07/21/2017

Print Date: 12/7/2017

SDS Number: R0388288

SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil

Version: 2.0

VV981

Acute inhalation toxicity : **LC50 (Rat): > 5.2 mg/l**
Exposure time: **4 h**
Test atmosphere: **dust/mist**
Assessment: **Not classified as acutely toxic by inhalation under GHS.**

Acute dermal toxicity : **LD50 (Rat): > 2,000 mg/kg**
Assessment: **Not classified as acutely toxic by dermal absorption under GHS.**

ORGANIC COMPOUND:

Acute oral toxicity : **LD50 (Rat): > 2,000 mg/kg**
Method: **OECD Test Guideline 401**
Assessment: **Not classified as acutely toxic by ingestion under GHS.**
Remarks: **No mortality observed at this dose.**

Acute dermal toxicity : **LD50 (Rat): > 2,000 mg/kg**
Method: **OECD Test Guideline 402**
Assessment: **Not classified as acutely toxic by dermal absorption under GHS.**
Remarks: **No mortality observed at this dose.**

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Acute oral toxicity : **LD50 (Rat): ca. 2,000 mg/kg**
Method: **OECD Test Guideline 401**
Assessment: **The component/mixture is classified as acute oral toxicity, category 4.**

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

ORGANIC COMPOUND:

Result: **No skin irritation**

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

POLYMER:

Species: **Rabbit**

Result: **No skin irritation**

	Page: 10
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

ORGANIC COMPOUND:

Result: **Mild skin irritation**

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ORGANIC COMPOUND:

Result: **No eye irritation**

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

POLYMER:

Species: **Rabbit**

Result: **Slight, transient irritation**

ORGANIC COMPOUND:

Result: **Slight, transient irritation**

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Result: **Corrosive**

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

POLYMER:

Test Type: **Maximisation Test**

Species: **Guinea pig**

Assessment: **Does not cause skin sensitisation.**

ORGANIC COMPOUND:

Test Type: **Maximisation Test**

Species: **Guinea pig**

Assessment: **The product is a skin sensitiser, sub-category 1B.**

Method: **OECD Test Guideline 406**

	Page: 11
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Test Type: **Local lymph node assay**
Species: **Mouse**
Method: **OECD Test Guideline 429**
Result: **May cause sensitisation by skin contact.**

Germ cell mutagenicity

Not classified based on available information.

Components:

ORGANIC COMPOUND:

Genotoxicity in vitro : Test Type: **Ames test**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

: Test Type: **Chromosome aberration test in vitro**
Test species: **Human lymphocytes**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Genotoxicity in vivo : Test Type: **Micronucleus test**
Test species: **Mouse**
Application Route: **Intraperitoneal injection**
Result: **negative**

POLYMER:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

ORGANIC COMPOUND:

Genotoxicity in vitro : Test Type: **in vitro assay**
Result: **Positive results were obtained in some in vitro tests.**

Genotoxicity in vivo : Test Type: **Micronucleus test**
Test species: **Mouse**
Cell type: **Bone marrow**
Method: **OECD Test Guideline 474**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

	Page: 12
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Reproductive toxicity

Components:

ORGANIC COMPOUND:

Species: **Rat**

No observed adverse effect level: 1000 mg/kg

Application Route: **Oral**

Exposure time: **28-day**

Aspiration toxicity

Not classified based on available information.

Components:

Mineral Oil:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ORGANIC COMPOUND:

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l**
Exposure time: **96 h**
Test Type: **semi-static test**
Test substance: **WAF**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Water flea (Daphnia magna)): > 1,000 mg/l**
Exposure time: **48 h**
Test Type: **static test**
Test substance: **WAF**

POLYMER:

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l**
Exposure time: **96 h**
Test Type: **semi-static test**
Test substance: **WAF**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea)): > 1,000 mg/l**
Exposure time: **48 h**
Test Type: **static test**

SAFETY DATA SHEET

Revision Date: 07/21/2017

Print Date: 12/7/2017

SDS Number: R0388288

SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil

Version: 2.0

VV981

Test substance: WAF

ORGANIC COMPOUND: Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Toxicity to fish : LL50 (*Oncorhynchus mykiss* (rainbow trout)): ca. 24 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Water flea* (*Daphnia magna*)): ca. 91.4 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): 15 mg/l
End point: Growth inhibition
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 3.3 mg/l
End point: Growth inhibition
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Water flea* (*Daphnia magna*)): 0.12 mg/l
Exposure time: 21 d
End point: Reproduction Test
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

No data available

Persistence and degradability

Components:

ORGANIC COMPOUND:

Biodegradability : Result: Not readily biodegradable.

SAFETY DATA SHEET

Revision Date: 07/21/2017

Print Date: 12/7/2017

SDS Number: R0388288

SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil

Version: 2.0

VV981

Biodegradation: 51.9 %

Exposure time: 28 d

POLYMER:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 19 %

Exposure time: 28 d

ORGANIC COMPOUND:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 13 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 7.4 %

Exposure time: 28 d

Method: Modified Sturm Test

No data available

Bioaccumulative potential

Components:

ORGANIC COMPOUND:

Partition coefficient: n-octanol/water : log Pow: 5

POLYMER:

Partition coefficient: n-octanol/water : log Pow: > 4

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Partition coefficient: n-octanol/water : Remarks: No data available

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., May cause long lasting harmful effects to aquatic life.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/21/2017
		Print Date: 12/7/2017
		SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil		Version: 2.0
VV981		

- General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	MARINE POLLUTANT:(DI-TERT-BUTYL POLYSULFID E)

UN_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

	Page: 16
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO)	: Not applicable
Priority Chemical List (PCL)	: Not applicable
Hazardous Substance Act B.E. 2535	: Not applicable
Emergency Decree on Controlling the Use of Volatile Substances B.E. 2533	: Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/21/2017

Full text of H-Statements

H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H316	Causes mild skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H401	Toxic to aquatic life.
H402	Harmful to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

	Page: 17
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil	Version: 2.0
VV981	

H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average

	Page: 18
SAFETY DATA SHEET	Revision Date: 07/21/2017
	Print Date: 12/7/2017
	SDS Number: R0388288
SynPower™ SAE Limited Slip SAE 75W-140 Synthetic Gear Oil VV981	Version: 2.0

vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CEATOX
Assistance Center of the Institute of Toxicology
Children's Hospital Clinic, Faculty of Medicine
University of São Paulo.
BR OEL : Occupational Exposure Limit (Brazil)
UY OEL : Occupational Exposure Limit (Uruguay)
PY OEL : Occupational Exposure Limit (Paraguay)