

PowerShield[®] Break-In Motor Oil

Part No. 4270H - 32-ounce HDPE container

Purpose Built Performance

Champion® Power Shield Break-In Motor Oil is specially designed to reduce the potential of engine failure during hard break-in. This formulation is based on the performance achievements of Champion PowerShield Engine Assembly Lube & Oil Booster.

This product contains high levels of zinc-thiophosphates, in combination with Champion's proprietary TVS® (Thermal Viscosity Stabilizer), which extends oil film capacity for proper ring seating. Professional engine-builders that use Champion® Power Shield Break-In Motor Oil will see the difference of our proven barrier of protection and is recommended for all types engines including flat-tappet or roller cams.

• Designed for tight clearance hard break-in to maximize compression and torque

• Protects cams and lifters permitting high temperature ring sealing

• Best performance in class among methanol and high-octane race engines

• Requires no additional additives

 After break-in, engine builders recommend Champion[®] Racing or Champion[®] Hot Rod Oils

Typical Properties	
MSDS #	100
Lbs./Gal.	7.45
Gravity	0.898
Vk100	12.0
Anti-wear Elements	
Zn, %wt	0.256
Ca, %wt	0.173
Flash Pt., °C (°F)	250 (482)
Pour Pt., °C (°F)	-18 (0)



FOR MORE INFORMATION, CALL (800) 821-5693

Champion Brands, LLC 1001 Golden Drive, Clinton MO 64735

