

acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

SECTION 1: Identification

1.1 Product identifier

Trade name Boyd Coddington Garage Ultra Tire Dressing

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses tire/rubber dressing

1.3 Details of the supplier of the safety data sheet

B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States

Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com

Website: bbblending.com

Competent person responsible for the SDS

e-mail (competent person) bblahnik@bbblending.com

o man (competent percent)

1.4 Emergency telephone number Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency telephone number.

Robert Blahnik

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification in accordance with Regulation No 1272/2008/EC.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

not required

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

SECTION 4: First-aid measures

4.1 Description of firs- aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

Provide fresh air.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water spray, alcohol resistant foam, BC-powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NOx), carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage (sawdust, kieselgur (diatomite), sand, universal binder).

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not to eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

Incompatible substances or mixtures

Observe compatible storage of chemicals.

Control of the effects

Protect against external exposure, such as

frost

Consideration of other advice

Packaging compatibilities

Only packagings which are approved (e.g. acc. to DOT) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

| Coun- try | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m³] | STEL [ppm] | STEL [mg/m³] | Source |
|--------------|-----------------|---------|------------|--------------|----------------|---------------|-----------------|-------------|
| US | glycerin (mist) | 56-81-5 | PEL | | 15 | | | 29 CFR OSHA |
| US | glycerin (mist) | 56-81-5 | PEL | | 5 | | | 29 CFR OSHA |

Notation

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless other-

wise specified

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted av-

erage.

Relevant DNELs/DMELs/PNECs and other threshold levels

No data available.

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state liquid Color white

Odor citrus - fresh

Other physical and chemical parameters

pH (value) 7 - 8.5 (25 °C)

Melting point/freezing point not determined

Initial boiling point and boiling range 100 °C at 1 atm

Flash point not determined (closed cup)

Evaporation rate not determined Flammability (solid, gas) not relevant (fluid)

Explosive limits

lower explosion limit (LEL)
 upper explosion limit (UEL)
 19 vol%

Vapor pressure 31.69 hPa at 25 °C

Density 1 g/ml

Relative density 0.98 - 1.02 water = 1 at 25 °C

Solubility(ies) not determined

Partition coefficient

n-octanol/water (log KOW)

This information is not available.

Auto-ignition temperature 370 °C

Viscosity not determined

Explosive properties none
Oxidizing properties none

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2)

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Physical stresses which might result in a hazardous situation and have to be avoided strong shocks

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

not relevant

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant.

Carcinogenicity

• National Toxicology Program (United States):

none of the ingredients are listed

IARC Monographs

none of the ingredients are listed

Specific target organ toxicity (STOT)

Shall not be classified as a specific target organ toxicant.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Date of compilation: 2015-12-10



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

| 14 | .1 | ı | ΙN | nı | ım | her | • |
|----|----|---|----|----|----|-----|---|

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es)

Class

ass

14.4 Packing group not relevant

14.5 Environmental hazards none (non-environmentally hazardous acc. to the dangerous goods regu-

lations)

14.6 Special precautions for user

There is no additional information.



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2)

Date of compilation: 2015-12-10

Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question 15.1 **National regulations (United States)**

Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

SARA TITLE III (Superfund Amendment and Reauthorization Act)

List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section none of the ingredients are listed 302 and 304)

Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313) none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System (American Coatings Association)

| Category | Rating | Description |
|-------------------------------|--------|---|
| Chronic | * | Chronic (long-term) health effects may result from repeated overexposure. |
| Health | 0 | No significant risk to health. |
| Flammability | 0 | Material that will not burn under typical fire conditions. |
| Physical hazard | 0 | Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive. |
| Personal protective equipment | - | |

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States)

| Category | Degree of hazard | Description |
|----------------|------------------|--|
| Flammability | 1 | Material that must be preheated before ignition can occur. |
| Health | 0 | Material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material. |
| Instability | 0 | Material that is normally stable, even under fire conditions. |
| Special hazard | | |

Proposition 65 List of chemicals

none of the ingredients are listed



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

SECTION 16: Other information, including date of preparation or last revision

16.1 Indication of changes (revised safety data sheet)

| Section | Former entry (text/value) | Actual entry (text/value) | Safety- relevant |
|---------|---|--|---------------------|
| 1.1 | Trade name: Detail King Blue Hawaii | Trade name: Detail King Pearl Gloss | yes |
| 1.3 | Details of the supplier of the safety data sheet: Detail King 947-A Old Frankstown Rd Pittsburgh, PA 15239 nvacco@detailking.com 888-314-0847 | Details of the supplier of the safety data sheet: B&B Blending, LLC 10963 Leroy Drive Northglenn CO 80233 United States Telephone: 1.800.875.6320, 1.303.289.6320 Telefax e-mail: info@bbblending.com Website: bbblending.com | yes |
| 1.3 | | e-mail (competent person): bblahnik@bbblending.com | yes |

16.2 Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|----------------------|---|
| 29 CFR OSHA | 29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits) |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| CMR | Carcinogenic, Mutagenic or toxic for Reproduction |
| DMEL | Derived Minimal Effect Level |
| DNEL | Derived No-Effect Level |
| DOT | Department of Transportation (USA) |
| IARC Mono- graphs | IARC Monographs on the Evaluation of Carcinogenic Risks to Humans |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant) |
| NFPA® 704 | National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States) |
| NPCA-HMIS® | National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition |
| OSHA | Occupational Safety and Health Administration (United States) |
| PBT | Persistent, Bioaccumulative and Toxic |
| PEL | permissible exposure limit |
| PNEC | Predicted No-Effect Concentration |
| ppm | parts per million |
| STEL | short-term exposure limit |
| TWA | time-weighted average |
| vPvB | very Persistent and very Bioaccumulative |



acc. to OSHA, Appendix D to § 1910.1200

Boyd Coddington Garage Ultra Tire Dressing

Version number: GHS 3.0 Replaces version of: 2015-08-06 (GHS 2) Date of compilation: 2015-12-10

16.3 Key literature references and sources for data

- OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200
- 49 CFR § 172.101 Hazardous Materials Table (DOT)

16.4 Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards/Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

16.5

List of relevant phrases (code and full text as stated in chapter 2 and 3)

16.7 Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.